



ZPMV2.E103967 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

FIMA S R L
 VIALE DEL LAVOR 20
 36100 VICENZA, VI ITALY

E103967

| Type | Cond Width | | Cond Thk mic(mil) | SS/ DS/ DSO | Max | Max | | Meets C UL796 DSR | C | I | |
|--|---------------|-----------------------|----------------------|-------------------|------------------------|-----------------------|-------------------|-------------------------|-----|-----|----------------|
| | Min mm(in) | Min Edge mm(in) | | | Area Diam mm(in) | Solder Limits C | Oper Temp C | | | | Flame Class |
| Multilayer printed wiring boards. | | | | | | | | | | | |
| 102 | 0.08 (0.003) | 0.1 (0.004) | 16.5 (0.65) Int:66 | DS | 50.8 (2.0) | 270 | 10 | 120 | V-0 | All | 3 |
| 103 | 0.08 (0.003) | 0.1 (0.004) | 16.5 (0.65) Int:132 | DS | 50.8 (2.0) | 260 | 10 | 110 | V-0 | All | 3 |
| 125 ML LF1 | 0.1 (0.004) | 0.1 (0.004) | 16.5 (0.65) Int:66 | DS | 76.2 (3.0) | 288 | 10 | 125 | V-0 | All | * |
| 125 ML LF2 | 0.1 (0.004) | 0.1 (0.004) | 16.5 (0.65) Int:66 | DS | 76.2 (3.0) | 288 | 10 | 125 | V-0 | All | * |
| 130 ML LF | 0.07 (0.003) | 0.12 (0.005) | 16.5 (0.65) Int:66 | DS | 76.2 (3.0) | 288 | 10 | 130 | V-0 | All | * |
| 130ML | 0.1 (0.004) | 0.1 (0.004) | 16.5 (0.65) Int:99 | DS | 50.8 (2.0) | 260 | 10 | 130 | V-0 | All | * |
| Printed Wiring Boards. | | | | | | | | | | | |
| 10 RO | 0.25 (0.010) | 0.25 (0.010) | 17 (0.67) Int:0 | DS | 76.2 (3.0) | 274 | 10 | 115 | V-0 | All | 0 |
| Single layer printed wiring boards. | | | | | | | | | | | |
| 101 | 0.08 (0.003) | 0.1 (0.004) | 16.5 (0.65) | DS | 50.8 (2.0) | 270 | 10 | 120 | V-0 | All | 4 |
| 101A | 0.08 (0.003) | 0.1 (0.004) | 16.5 (0.65) | DS | 50.8 (2.0) | 270 | 10 | 120 | V-0 | All | 1 |
| 125 LF1 | 0.1 (0.004) | 0.1 (0.004) | 16.5 (0.65) | DS | 76.2 (3.0) | 288 | 10 | 125 | V-0 | All | * |
| 125 LF2 | 0.1 (0.004) | 0.1 (0.004) | 16.5 (0.65) | DS | 76.2 (3.0) | 288 | 10 | 125 | V-0 | All | * |
| 130 | 0.1 (0.004) | 0.1 (0.004) | 16.5 (0.65) | DS | 50.8 (2.0) | 260 | 10 | 130 | V-0 | All | * |
| 130LF | 0.07 (0.003) | 0.12 (0.005) | 16.5 (0.65) | DS | 76.2 (3.0) | 288 | 10 | 130 | V-0 | All | * |

NOTE - A triangle is marked on those products within a given type designation that comply with direct support of current-carrying parts performance level requirements of UL 796. "All" is used to indicate that all base materials under that type designation comply with direct support of current-carrying parts performance level requirement of UL796.

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or tradename "FSRL" or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"